



VIEW INFORMATION RIGHT BEFORE YOUR EYES

☀ EVEN IN THE BRIGHTEST DAYLIGHT ☀

Increase your productivity.

Whether you're on the construction site, manufacturing floor or providing in-field service, tap into your computer's information and read it right in front of you. Introducing the SV-6 PC Viewer by MicroOptical. This lightweight viewer easily attaches to prescription or safety eyewear — allowing you to view task-specific data while maintaining your natural field of vision. Focus on your work without repeatedly diverting your attention to your computer screen or hand-held monitor. And the SV-6 frees your hands — making it easier to perform your tasks. Exhibiting unparalleled clarity and outperforming traditional LCD monitors, the SV-6's display can be read easily even in the brightest sunlight. So why stare at glare? If you'd like to increase the productivity of your workforce, call MicroOptical today at 781.326.8111. See what you've been missing.




 **MicroOptical**


MAKING PORTABLE PRACTICAL.™

www.MicroOptical.net

©2003 The MicroOptical Corporation. "Making portable practical." is a trademark of The MicroOptical Corporation.



APPLICATIONS BENEFITING FROM MOBILE INFORMATION VIEWING



PRODUCT SPECIFICATIONS

	SV-6 PC Viewer	SV-3 Instrument Viewer
Display Format	640 x 480, 60 Hz refresh rate, landscape	
Color Depth	18-Bit (262,144 colors)	6-Bit (64 colors)
Optics Location	Left or right eye configurable	
Field of View	Approximately 16° horizontal, 20° diagonal	
Focus Range	Adjustable focus from 2 to 15 feet	
Input Signal	VGA, SVGA, X VGA, 60-75 Hz	VGA, 60 Hz
Input Connector	Standard VGA, male DB-15 connector, 18" cable	
Power Requirements	2 W	950 mW
Power Source	7.2 V lithium ion rechargeable battery	
Continuous Operation	5 hours on full charge	8 hours on full charge
Viewer Weight	1.25 ounces (35 grams)	
Cable Length	4 feet from the viewer to the belt-worn battery	
Eyeglass Frame Size	Fits many std. eyeglasses/safety glasses w/ quick release mount	
Operating Temperature	32 to 140°F (0 to 60°C)	
Storage Temperature	-4 to 140°F (-20 to 60°C)	



Included with the SV-6 and SV-3 viewers: mounting kit for use with alternative eyewear, rechargeable lithium ion battery, battery charger, 6 ft. VGA extension cable, optical cloth, user's manual, belt-worn pouch, velour pouch, screwdriver, croakie, UVEX safety eyewear and hard shell carrying case.



Belt-Worn Battery
Dimensions: 3" x 2" x 0.5"



www.MicroOptical.net

The MicroOptical Corporation, 33 Southwest Park, Westwood, MA 02090
t: 781.326.8111 f: 781.326.4110

©2003 The MicroOptical Corporation. "Making portable practical" is a trademark of The MicroOptical Corporation. Protected by U.S. Patents 5715377, 5886822, 6023372, 6091546, and other U.S. and International Patents Pending.